

General Description

The SDC141 is a lock-type switch hall IC. It's composed of power reverse protection circuit, high stable voltage regulator, hall voltage generator, a differential amplifier, schmitt trigger and open collector output. Change of magnetic field can be converted into digital signal. It can be used for brushless DC three-phase motors, brushless DC fans, and speed measurement occasions.

Features

- Operating voltage: 4V to 24 V
- Built-in temperature compensation circuit
- Built-in power reverse protection
- Operating temperature: -55°C~150°C
- Open collector output
- 20mA(MAX) output sink current
- Operating speed: 0~100kHz above
- Package: TO-92S、SOT23-3

Applications

- Three-phase brushless DC motor
- Brushless DC fan
- Tachometer
- Speed measurement





Figure 1. Package Type

Pin Configuration

Package: TO-92S



Package: SOT-23-3




Figure 2. Pin Configuration

Pin Number		Pin Name	Function
SOT-23-3	TO-92S		
1	1	VCC	Supply voltage pin
3	2	GND	Ground pin
2	3	OUT	Output pin

Table 1. Pin Description



Functional Block Diagram


Figure 3. Functional Block Diagram

Ordering Information


Package	Temperature Range	Part Number		Marking ID		Packing Type
		Pb-free	Halogen-free	Pb-free	Halogen-free	
TO-92S	-55°C~150°C	SDC141AZS-E1	SDC141AZS-G1	S41	S41G	Bulk
		SDC141aZS-E1	SDC141aZS-G1	S41	S41G	Bulk
		SDC141BZS-E1	SDC141BZS-G1	S41	S41G	Bulk
SOT-23-3		SDC141AJTR-E1	SDC141AJTR-G1	S41	S41G	Tape Reel
		SDC141aJTR-E1	SDC141aJTR-G1	S41	S41G	Tape Reel
		SDC141BJTR-E1	SDC141BJTR-G1	S41	S41G	Tape Reel

Absolute Maximum Ratings (NOTE: Stresses greater than those listed under absolute maximum ratings may cause permanent damage to the device.)

Parameter	Symbol	Value	Unit
Supply voltage	V_{CC}	30	V
Magnetic flux density	B	-	mT
Output breakdown voltage	V_{CE}	60	V
Output current	I_{OL}	40	mA
Storage temperature range	T_S	-55 to 170	°C
Power dissipation	P_D	550	mW
Maximum junction temperature	T_J	150	°C
ESD,HBM model per MIL-STD-883H Method 3015.8	HBM	6000	V
ESD,MM model per JEDEC EIA/JESD22-A115	MM	600	V
Latch-up per JEDEC78	-	200	mA

Table 2. Absolute Maximum Ratings

Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Power supply	V_{CC}	4	24	V
Operation temperature	T_a	-55	150	°C

Table 3. Recommended Operating Conditions

Electrical Characteristics ($T_a=25^\circ\text{C}$, $V_{CC}=4.5\text{V}$, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Supply voltage	V_{CC}	-	4	-	24	V
Output saturation voltage	V_{OUT}	$I_{OUT}=20\text{mA}$, $B>B_{OP}$	-	200	400	mV
Output leakage current	I_{OFF}	$V_{CE}=30\text{V}$, $B<B_{RP}$	-	0.1	10	μA
Supply current	I_{CC1}	$V_{CC}=4.5\text{V}$, output open	-	2.5	5	mA
	I_{CC2}	$V_{CC}=24\text{V}$, output open	-	4.0	6	mA
Output rise time	t_r	R_L to VCC, C_L to GND $R_L=820\Omega$, $C_L=20\text{pF}$	-	0.25	1.5	μs
Output fall time	t_f	R_L to VCC, C_L to GND $R_L=820\Omega$, $C_L=20\text{pF}$	-	0.50	1.5	μs

Table 4. Electrical Characteristics

Magnetic Characteristics ($V_{CC}=4.5\text{V}$, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Operating point	B_{OP}	$T_a=120^\circ\text{C}$	15	65	110	GS
		$T_a=25^\circ\text{C}$	10	50	90	GS
Release point	B_{RP}	$T_a=120^\circ\text{C}$	-110	-65	-15	GS
		$T_a=25^\circ\text{C}$	-90	-50	-10	GS
Hysteresis	B_H	$T_a=120^\circ\text{C}$	120	130	140	GS
		$T_a=25^\circ\text{C}$	90	100	110	GS

Table 5. Magnetic Characteristics

Note: when S pole of magnetic is faced to the marked side of IC, the magnetic field is positive.

Grade A

Parameter	Symbol	Min	Max	Unit
Operate point	B_{OP}	35	75	GS
Release point	B_{RP}	-140	-15	GS

Grade a

Parameter	Symbol	Min	Max	Unit
Operate point	B_{OP}	75	140	GS
Release point	B_{RP}	-140	-15	GS

Grade B

Parameter	Symbol	Min	Max	Unit
Operate point	B_{OP}	15	35	GS
Release point	B_{RP}	-140	-15	GS




Figure 4. Magnetic Characteristics

Typical Application






Figure 5. Typical Application

Package Dimensions
SOT-23-3


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

TO-92S


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.420	1.620	0.056	0.064
A1	0.660	0.860	0.026	0.034
b	0.350	0.480	0.014	0.019
b1	0.380	0.530	0.015	0.021
c	0.360	0.510	0.014	0.020
D	3.900	4.100	0.154	0.161
D1	2.970	3.270	0.117	0.129
E	2.900	3.100	0.116	0.124
e	1.270 TYP.		0.050 TYP.	
e1	2.440	2.640	0.096	0.104
L	14.500	14.900	0.580	0.596
θ	45° TYP.		45° TYP.	

**Shaoxing Devechip Microelectronics Co., Ltd.**

<http://www.sdc-semi.com/>

IMPORTANT NOTICE

Information in this document is provided solely in connection with Shaoxing Devechip Microelectronics Co., Ltd. (abbr. SDC) products. SDC reserves the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at anytime, without notice. SDC does not assume any responsibility for use of any its products for any particular purpose, nor does SDC assume any liability arising out of the application or use of any its products or circuits. SDC does not convey any license under its patent rights or other rights nor the rights of others.

© 2013 Devechip Microelectronics - All rights reserved

Contact us:**Headquarters of Shaoxing**

Address: Tian Mu Road, No13,
Shaoxing city, Zhejiang province, China
Zip code: 312000
Tel: (86) 0575-8861 6750
Fax: (86) 0575-8862 2882

Shenzhen Branch

Address: 22A, Shangbu building, Nan Yuan Road, No.68,
Futian District, Shenzhen city, Guangdong province, China
Zip code: 518031
Tel: (86) 0755-8366 1155
Fax: (86) 0755-8301 8528