


N-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

BV <sub>DSS</sub>	60V
R <sub>DSON</sub> (MAX.)	60mΩ
I <sub>D</sub>	3.5A



UIS, R<sub>G</sub> 100% Tested

Pb-Free Lead Plating & Halogen Free



**ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25 °C Unless Otherwise Noted)**

PARAMETERS/TEST CONDITIONS	SYMBOL	LIMITS	UNIT
Gate-Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current	I <sub>D</sub>	3.5	A
		2.3	
Pulsed Drain Current <sup>1</sup>	I <sub>DM</sub>	14	
Power Dissipation	P <sub>D</sub>	1.25	W
		0.83	
Operating Junction & Storage Temperature Range	T <sub>j</sub> , T <sub>stg</sub>	-55 to 150	°C

**THERMAL RESISTANCE RATINGS**

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Ambient	R <sub>θJA</sub>		100	°C / W

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>Duty cycle ≤ 1%







ELECTRICAL CHARACTERISTICS ( $T_c = 25^\circ\text{C}$ , Unless Otherwise Noted)






PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{GS} = 0V, I_D = 250\mu\text{A}$	60			V
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1.0	2.0	3.2	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 48V, V_{GS} = 0V$			1	$\mu\text{A}$
		$V_{DS} = 40V, V_{GS} = 0V, T_J = 125^\circ\text{C}$			25	
On-State Drain Current <sup>1</sup>	$I_{D(\text{ON})}$	$V_{DS} = 5V, V_{GS} = 10V$	3.5			A
Drain-Source On-State Resistance <sup>1</sup>	$R_{DS(\text{ON})}$	$V_{GS} = 10V, I_D = 3A$		50	60	$\text{m}\Omega$
		$V_{GS} = 5V, I_D = 2A$		58	75	
Forward Transconductance <sup>1</sup>	$g_{fs}$	$V_{DS} = 5V, I_D = 3A$		12		S
<b>DYNAMIC</b>						
Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = 30V, f = 1\text{MHz}$		633		$\text{pF}$
Output Capacitance	$C_{oss}$			67		
Reverse Transfer Capacitance	$C_{rss}$			44		
Total Gate Charge <sup>1,2</sup>	$Q_g$	$V_{DS} = 30V, V_{GS} = 10V, I_D = 3A$		13.8		$\text{nC}$
Gate-Source Charge <sup>1,2</sup>	$Q_{gs}$			2.8		
Gate-Drain Charge <sup>1,2</sup>	$Q_{gd}$			4.0		
Turn-On Delay Time <sup>1,2</sup>	$t_{d(\text{on})}$	$V_{DS} = 30V, I_D = 1A, V_{GS} = 10V, R_{GS} = 6\Omega$		10		$\text{nS}$
Rise Time <sup>1,2</sup>	$t_r$			12		
Turn-Off Delay Time <sup>1,2</sup>	$t_{d(\text{off})}$			20		
Fall Time <sup>1,2</sup>	$t_f$			15		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (<math>T_c = 25^\circ\text{C}</math>)</b>						
Continuous Current	$I_S$				2	$\text{A}$
Pulsed Current <sup>3</sup>	$I_{SM}$				8	
Forward Voltage <sup>1</sup>	$V_{SD}$	$I_F = I_S, V_{GS} = 0V$			1.2	V

<sup>1</sup>Pulse test : Pulse Width  $\leq 300 \mu\text{sec}$ , Duty Cycle  $\leq 2\%$ .

<sup>2</sup>Independent of operating temperature.


<sup>3</sup>Pulse width limited by maximum junction temperature.






Ordering & Marking Information:

Device Name: EMB60N06J for SOT-23



Outline Drawing



Dimension in mm

Dimension	A	A1	A2	b	C	D	E	E1	e	e1	F	G	L1
Min.	0.7	0		0.35	0.1	2.8	2.6	1.5	0.9		0.8	0.3	0.55
Typ.						2.9	2.8	1.6	0.95	1.9			
Max.	1.12	0.1		0.5	0.2	3	3	1.7	1		1.2	0.6	0.65

Footprint

