



P-Channel Logic Level Enhancement Mode Field Effect Transistor

Product Summary:

$BV_{DSS}$	-30V
$R_{DS(on)} (MAX.)$	3.3m $\Omega$
$I_D$	-85A



UIS, Rg 100% Tested

Pb-Free Lead Plating & Halogen Free



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$  Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNIT
Gate-Source Voltage		$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$T_C = 25^\circ\text{C}$	$I_D$	-85	A
	$T_C = 100^\circ\text{C}$		-65	
Pulsed Drain Current <sup>1</sup>		$I_{DM}$	-260	
Avalanche Current		$I_{AS}$	-80	
Avalanche Energy	$L = 0.1\text{mH}, I_D = -80\text{A}, R_G = 25\Omega$	$E_{AS}$	320	mJ
Repetitive Avalanche Energy <sup>2</sup>	$L = 0.05\text{mH}$	$E_{AR}$	160	
Power Dissipation	$T_C = 25^\circ\text{C}$	$P_D$	121	W
	$T_C = 100^\circ\text{C}$		48	
Operating Junction & Storage Temperature Range		$T_{j}, T_{stg}$	-55 to 150	$^\circ\text{C}$

100% UIS testing in condition of  $V_D = -15\text{V}, L = 0.1\text{mH}, V_G = -10\text{V}, I_L = -50\text{A}$ , Rated  $V_{DS} = -30\text{V}$  P-CH

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	$R_{\theta JC}$		1.03	$^\circ\text{C} / \text{W}$
Junction-to-Ambient <sup>3</sup>	$R_{\theta JA}$		62.5	

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>Duty cycle  $\leq 1\%$



ELECTRICAL CHARACTERISTICS ( $T_J = 25\text{ }^\circ\text{C}$ , Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1	-1.5	-3	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -24V, V_{GS} = 0V$			-1	$\mu A$
		$V_{DS} = -20V, V_{GS} = 0V, T_J = 125\text{ }^\circ\text{C}$			-10	
On-State Drain Current <sup>1</sup>	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -10V$	-85			A
Drain-Source On-State Resistance <sup>1</sup>	$R_{DS(ON)}$	$V_{GS} = -10V, I_D = -30A$		2.9	3.3	m $\Omega$
		$V_{GS} = -4.5V, I_D = -30A$		4.2	5.2	
Forward Transconductance <sup>1</sup>	$g_{fs}$	$V_{DS} = -5V, I_D = -30A$		70		S
<b>DYNAMIC</b>						
Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = -15V, f = 1MHz$		6400		pF
Output Capacitance	$C_{oss}$			913		
Reverse Transfer Capacitance	$C_{rss}$			656		
Gate Resistance	$R_g$	$V_{GS} = 15mV, V_{DS} = 0V, f = 1MHz$		3.4		$\Omega$
Total Gate Charge <sup>1,2</sup>	$Q_g$	$V_{DS} = -15V, V_{GS} = -10V,$ $I_D = -30A$		96.5		nC
Gate-Source Charge <sup>1,2</sup>	$Q_{gs}$			24.8		
Gate-Drain Charge <sup>1,2</sup>	$Q_{gd}$			13.8		
Turn-On Delay Time <sup>1,2</sup>	$t_{d(on)}$	$V_{DS} = -15V,$ $I_D = -1A, V_{GS} = -10V, R_{GS} = 2.7\Omega$		15		nS
Rise Time <sup>1,2</sup>	$t_r$			20		
Turn-Off Delay Time <sup>1,2</sup>	$t_{d(off)}$			130		
Fall Time <sup>1,2</sup>	$t_f$			55		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (<math>T_C = 25\text{ }^\circ\text{C}</math>)</b>						
Continuous Current	$I_S$				-85	A
Pulsed Current <sup>3</sup>	$I_{SM}$				-260	
Forward Voltage <sup>1</sup>	$V_{SD}$	$I_F = -30A, V_{GS} = 0V$			-1.2	V
Reverse Recovery Time	$t_{rr}$	$I_F = I_S, dI_F/dt = 100A / \mu S$		26		nS
Reverse Recovery Charge	$Q_{rr}$			80		nC


<sup>1</sup>Pulse test : Pulse Width  $\leq 300 \mu\text{sec}$ , Duty Cycle  $\leq 2\%$ .

<sup>2</sup>Independent of operating temperature.


<sup>3</sup>Pulse width limited by maximum junction temperature.

### Ordering & Marking Information:

Device Name: EMB03P03A for DPAK (TO-252)



### Outline Drawing



Dimension in mm

Dimension	A	A1	B	B1	B2	C	D	D2	D3	E	E2	H	L	L1	L2	L3	P
Min.	2.10	0.95	0.30	0.40	0.60	0.40	5.30	6.70	2.20	6.40	4.80	9.20	0.89	0.90	0.50	0.00	2.10
Max.	2.50	1.30	0.85	0.94	1.00	0.60	6.20	7.30	3.00	6.70	5.45	10.15	1.70	1.65	1.10	0.30	2.50

