





- ▼ Simple Drive Requirement
- ▼ Small Size & Lower Profile
- ▼ RoHS Compliant & Halogen-Free



BV_{DSS}	-20V
$R_{DS(ON)}$	42mΩ
I_D^3	-7.3A



PMPAK® 3x3

Description

AP2335 series are from Advanced Power innovative design and silicon process technology to achieve the lowest possible on-resistance and fast switching performance. It provides the designer with an extreme efficient device for use in a wide range of power applications.

The PMPAK® 3 x 3 package is special for voltage conversion application using standard infrared reflow technique with the backside heat sink to achieve the good thermal performance.

Absolute Maximum Ratings@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	± 12	V
$I_D @ T_A=25^\circ\text{C}$	Drain Current, $V_{GS} @ 4.5\text{V}^3$	-7.3	A
$I_D @ T_A=70^\circ\text{C}$	Drain Current, $V_{GS} @ 4.5\text{V}^3$	-5.8	A
I_{DM}	Pulsed Drain Current ¹	-30	A
$P_D @ T_A=25^\circ\text{C}$	Total Power Dissipation	3.12	W
T_{STG}	Storage Temperature Range	-55 to 150	°C
T_J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Data

Symbol	Parameter	Value	Unit
R_{thj-c}	Maximum Thermal Resistance, Junction-case	8	°C/W
R_{thj-a}	Maximum Thermal Resistance, Junction-ambient ³	40	°C/W



Electrical Characteristics@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=-250\mu\text{A}$	-20	-	-	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance ²	$V_{\text{GS}}=-4.5\text{V}, I_{\text{D}}=-6\text{A}$	-	-	42	$\text{m}\Omega$
		$V_{\text{GS}}=-2.5\text{V}, I_{\text{D}}=-4\text{A}$	-	-	65	$\text{m}\Omega$
		$V_{\text{GS}}=-1.8\text{V}, I_{\text{D}}=-1\text{A}$	-	-	85	$\text{m}\Omega$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\mu\text{A}$	-0.3	-	-1.2	V
g_{fs}	Forward Transconductance	$V_{\text{DS}}=-5\text{V}, I_{\text{D}}=-6\text{A}$	-	14	-	S
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=-16\text{V}, V_{\text{GS}}=0\text{V}$	-	-	-10	uA
I_{GSS}	Gate-Source Leakage	$V_{\text{GS}}=+12\text{V}, V_{\text{DS}}=0\text{V}$	-	-	+0.1	uA
Q_g	Total Gate Charge	$I_{\text{D}}=-6\text{A}$	-	12	19.2	nC
Q_{gs}	Gate-Source Charge	$V_{\text{DS}}=-10\text{V}$	-	2.5	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{\text{GS}}=-4.5\text{V}$	-	3.5	-	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{DS}}=-10\text{V}$	-	10	-	ns
t_r	Rise Time	$I_{\text{D}}=-1\text{A}$	-	17	-	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time	$R_{\text{G}}=3.3\Omega$	-	40	-	ns
t_f	Fall Time	$V_{\text{GS}}=-5\text{V}$	-	40	-	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}$	-	1000	1600	pF
C_{oss}	Output Capacitance	$V_{\text{DS}}=-10\text{V}$	-	170	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	145	-	pF
R_g	Gate Resistance	f=1.0MHz	-	15	30	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	$I_{\text{S}}=-2.6\text{A}, V_{\text{GS}}=0\text{V}$	-	-	-1.2	V
t_{rr}	Reverse Recovery Time	$I_{\text{S}}=-6\text{A}, V_{\text{GS}}=0\text{V},$ $dI/dt=100\text{A}/\mu\text{s}$	-	11	-	ns
			-	4	-	nC

Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse test
- 3.Surface mounted on 1 in² copper pad of FR4 board, t ≤10sec ; 85°C at steady state.

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT, AUTOMOTIVE OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics





Fig 12. Drain Current v.s. Ambient Temperature



AP2335YT

MARKING INFORMATION



Part Number

Date Code (YWWSSS)

Y : Last Digit Of The Year
WW : Week
SSS : Sequence