



**PRODUCT SUMMARY**

$V_{(BR)DSS}$	$R_{DS(ON)}$	$I_D^3$
20V	5mΩ	47A



G : GATE  
D : DRAIN  
S : SOURCE

**ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25 °C Unless Otherwise Noted)**

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		$V_{DS}$	20	V
Gate-Source Voltage		$V_{GS}$	±8	V
Continuous Drain Current <sup>3</sup>	T <sub>C</sub> = 25 °C	$I_D$	47	A
	T <sub>C</sub> = 100 °C		30	
	T <sub>A</sub> = 25 °C		17	
	T <sub>A</sub> = 70 °C		14	
Pulsed Drain Current <sup>1</sup>		$I_{DM}$	70	
Avalanche Current		$I_{AS}$	38.6	
Avalanche Energy	L = 0.1mH	$E_{AS}$	74.6	mJ
Power Dissipation	T <sub>C</sub> = 25 °C	$P_D$	19	W
	T <sub>C</sub> = 100 °C		7	
	T <sub>A</sub> = 25 °C		2.6	
	T <sub>A</sub> = 70 °C		1.6	
Operating Junction & Storage Temperature Range		T <sub>j</sub> , T <sub>stg</sub>	-55 to 150	°C

**THERMAL RESISTANCE RATINGS**

THERMAL RESISTANCE		SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient <sup>2</sup>	t ≤ 10s	$R_{θJA}$		48	°C / W
Junction-to-Ambient <sup>2</sup>	Steady-State	$R_{θJA}$		60	
Junction-to-Case		$R_{θJC}$		6.5	

<sup>1</sup>Pulse width limited by maximum junction temperature.

<sup>2</sup>The value of  $R_{θJA}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub> = 25°C.

<sup>3</sup>Package limitation current is 22A


**ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25 °C, Unless Otherwise Noted)**

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	20			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	0.4	0.7	0.9	
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±8V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V			1	μA
		V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 55 °C			5	
Drain-Source On-State Resistance <sup>1</sup>	R <sub>DS(ON)</sub>	V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 5A		4.1	5	mΩ
		V <sub>GS</sub> = 2.5V, I <sub>D</sub> = 5A		4.7	5.7	
		V <sub>GS</sub> = 1.8V, I <sub>D</sub> = 5A		6	8.2	
Forward Transconductance <sup>1</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 5V, I <sub>D</sub> = 5A		70		S
<b>DYNAMIC</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 10V, f = 1MHz		4407		pF
Output Capacitance	C <sub>oss</sub>			469		
Reverse Transfer Capacitance	C <sub>rss</sub>			381		
Gate Resistance	R <sub>g</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 0V, f = 1MHz		0.7		Ω
Total Gate Charge <sup>2</sup>	Q <sub>g</sub>	V <sub>GS</sub> =4.5V, V <sub>DS</sub> = 10V, I <sub>D</sub> = 5A		49		nC
Gate-Source Charge <sup>2</sup>	Q <sub>gs</sub>			6		
Gate-Drain Charge <sup>2</sup>	Q <sub>gd</sub>			13		
Turn-On Delay Time <sup>2</sup>	t <sub>d(on)</sub>	V <sub>DD</sub> = 4.5V I <sub>D</sub> ≅ 5A, V <sub>GEN</sub> = 10V, R <sub>G</sub> = 6Ω		20		nS
Rise Time <sup>2</sup>	t <sub>r</sub>			25		
Turn-Off Delay Time <sup>2</sup>	t <sub>d(off)</sub>			180		
Fall Time <sup>2</sup>	t <sub>f</sub>			85		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T<sub>J</sub> = 25 °C)</b>						
Continuous Current <sup>3</sup>	I <sub>S</sub>				14	A
Forward Voltage <sup>1</sup>	V <sub>SD</sub>	I <sub>F</sub> = 5A, V <sub>GS</sub> = 0V			1	V
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 5A, di <sub>F</sub> /dt = 100A / μS		24		nS
Reverse Recovery Charge	Q <sub>rr</sub>				12	


<sup>1</sup>Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

<sup>2</sup>Independent of operating temperature.


**Output Characteristics**




**Transfer Characteristics**




**On-Resistance VS Temperature**




**Capacitance Characteristic**




**Gate charge Characteristics**




**Source-Drain Diode Forward Voltage**



**Safe Operating Area**



**Single Pulse Maximum Power Dissipation**



**Transient Thermal Response Curve**

